# **Agrotron 9340 TTV**

#### **Engine**

Deutz TTCD 7.8 LO6 Tier 3 Diesel Engine 6 Cyl/7775cc Twin Turbocharged/Intercooled NO AdBlue Electronically Controlled 4 Valves Per Cylinder Liquid/Oil Cooled Common Rail DCR injection System 336 hp Max power (ECE R-120) 20Hp Power Boost Torque 1372nm 100% Bio Diesel Compliant Engine Speed Programming Powercore Airfilter with Dust Ejectors Side exhaust 600 Lt Fuel Capacity

#### **Transmission**

ZF Terramatic CVT Transmission
4 Working Ranges
3 Driving Modes (Auto, PTO, Manual)
Acceleration and Power Adjustment
Speed Cruise Control
Active Stationary Control
Wet clutch Powershuttle with Modulation
Front Wheel Assist
4 Wheel Braking
Front Axle Suspension
Hydraulic Trailer Braking
Front & Rear Diff Lock
ASM Auto Diff Lock and 4wd Engagement
Radar
Separate Transmission Fluid Reservoir

#### PTO

Independent wet multidisc clutch 3 Speed PTO 540E/1000/1000E Push Button control on Armrest Auto PTO External PTO Start/Stop 1"3/4 20 Spline PTO Shaft 1"3/8 21 Spline PTO Spline Function

## **Wheel Equipment & Miscellaneous**

Fixed Radial Wheel Equipment
600/70R34 Front -710/75R42Rear
IF - Hi flex tyre equipment
Dynamic Front Fenders
Front Linkage - 5000kg capacity
Front lift with ground controls and electrical sockets
FP-PAC quick attach front weight(1400kg)
ISO 11783 Socket



## **Operator Environment**

Hi visibility MAXIVISION 2 Air Conditioned Cab Self Leveling Cabin with Pneumatic Suspension Max Comfort Dynamic XL Deluxe Air Seat Hi Visibility Glass Roof INFOCENTER Digital Display **COMFORTIP Sequential Drive System** Armrest Controls Padded Trainee Seat with Seatbelt EASY STEER adjustable steering Touchscreen i-Monitor Multifunction computer 1 Rear Camera Bluetooth MP3 Audio system WOLP (work operating light panel) Super Deluxe Cabin Work Light Package 2 Front LED lights on Bonnet Telescopic Mirrors Rotating Beacon

## **GPS System**

Autonomous 30cm System Hydraulic Auto Steer I-monitor 2 12.1" Touch Screen GLONASS Enabled ISOBUS ready with 11783 ISO Socket TIM ready (Tractor Implement Management)

## Hyd/Linkage

Load Sensing Hyd Pump System
160 L/min Hyd flow a Rear Remotes
Power Beyond Valve
Separate 42L/min Steering Pump
Separate Hydraulic Fluid Reservoir
4 Sets of Electro-Hyd Remotes
Flow Control and Timer on all Remotes
AGROTRONIC EHR with position & draft
Implement Ride Control
External Raise & lower on Rear Fenders
Cat III Hook ends
12000 kg lift capacity

#### Weights & Dimensions

| 3153mm  |
|---------|
| 5268mm  |
| 3500mm  |
| 12000kg |
|         |





