






		AGROPLUS F KEYLINE
TECHNICAL DATA		75
ENGINE		
Emissions		Tier3
Manufacturer		SDF 1000.3 WTI
Cylinders/Capacity	No./cm3	3/3,000
Turbo Intercooler intake		•
Max. homologated power (ECE R-120)	kW/hp	53/72
Max. engine speed (rated)	rpm	2,200
Max. torque	Nm	265
Mechanical engine control		•
Liquid cooling		•
Under-hood silencer with side exhaust		•
Fuel tank capacity	litres	65
Biodiesel fuel	%	B100
MECHANICAL GEARBOX		
Synchronised		•
Number of speeds with supercreeper gear	n°	12+3
Max. speed	km/h	30
Mechanical dry clutch, single		•
REAR PTO		
Mechanical dry clutch, single		•
Mechanical engagement		•
PTO 540/540ECO		•
FRONT AND REAR AXLE		
Front wheel drive mechanically engaged (for 4WD versions only)		•
Mechanically operated differential lock - front and rear		•
Steering angle/turning circle 4WD	degrees/mm	55°/4,680
BRAKES		
Braking system with wet brake discs		•
Mechanical parking brake		•
STEERING		
Hydrostatic steering with independent pump		•
Steering pump delivery	l/min	18
HITCH		
Category		II
Mechanical rear hitch		•
Rear hitch lift capacity	kg	2,845
HYDRAULIC SYSTEM		
Pump output	l/min	42
Open-centre hydraulic system		•
Mechanical distributor engagement		•
Rear hydraulic auxiliary valves	No. of ways	2 Sets
DRIVING POSITION		
Side control levers		•
Folding front roll bar		•
Driver seat with mechanical suspension		•
Analogue instrumentation		•
DIMENSIONS AND WEIGHTS		
Standard rear tyres		380/70R24
Max. length with rear linkage	mm	3,531
Max overall length. with rear linkage and roll bar folded down	mm	3,768
Width	mm	1,538
Wheelbase (4WD)	mm	1,996
Front track (4WD)	mm	1,297
Rear track	mm	1,221
Max. height with roll bar folded down	mm	2,372
Max. height at cowl	mm	1,468
Weight (4WD	kg	2,650
Maximum load capacity (4WD)	kg	4,800









STD ● OPT ○ - Not available



P+61 (3) 8353 3600 F+61 (3) 8353 3699

W www.deutztractors.com.au

199 Australis Drive, Derrimut, Victoria 3030

