

Agrofarm 420TB

Engine

Deutz 2012 Tier 3 Diesel Engine
4 Cyl/4038cc Turbocharged
Electronically Controlled
Liquid/Oil Cooled
High pressure Diesel injection
102 hp @ 2300 rpm (2005/25/CE)
Torque 380nm
100% Bio Diesel Compliant
Engine Speed Programming
Down swept exhaust
100lt Fuel Capacity

Transmission

40/40 Forward/Reverse gears
Wet clutch Powershuttle
2 Speed Powershift
Comfort Clutch
Creep Std
Front Wheel Assist
4 Wheel Independent Braking
100% Front & Rear Diff Lock
40 km/h Road speed

PTO

Independent wet multidisc clutch
4 Speed PTO 540/540E- 1000/1000E
Push Button control
1 3/8 -6 Spline PTO shaft
Interchangeable PTO Shaft Function

Wheel Equipment & Miscellaneous

Fixed Flootation Wheels
12*16.5 Front 500/60-22.5 Rear
Front Weight Frame



Operator Environment

Low Profile Air Conditioned Cab
Fold Down Rear ROPS frame
Ergonomic Controls
Multi Function Digital Dash
Deluxe Mechanical Sprung Seat
Rear Opening Glass window
Sprayer cable sealed access
Heavy Duty Rear Fender Extensions
Mirror kit
2 Rear Cabin Work lights
2 Bonnet Work lights

Hyd/Linkage

Open Centre Hyd Pump System
56 L/min Hyd a Rear Remotes
Separate 44L/min Steering Pump
3 Sets of Remotes – detent, float and Spring
Mechanical Linkage c/w position & draft controls
External Mechanical Raise & lower on Rear Fender
Cat 2 Hook Ends
4200 kg lift capacity

Weights & Dimensions

Wheelbase	2340mm
Length	4100mm
Total Height	2120mm
Total Weight	4140 kg

Effective July 2017